



REVISION		

ADPLEMCO
INCORPORATED

13702 SOUTH 200 WEST B9 DRAPER, UT 84020
WWW.ADPLEMCO.COM

PHONE (801) 280-4000
FAX (801) 280-4040
SALES@ADPLEMCO.COM

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY ADP LEMCO INC. IS STRICTLY PROHIBITED.

HEIGHT ADJUSTER - MANUAL

SIZE A	SCALE NONE	SHT. NO. 1 OF 1	PART NO. 125M	REV D
------------------	---------------	--------------------	-------------------------	-----------------

MODEL 125M

MANUAL HEIGHT ADJUSTER

APPLICATION

This unit is designed to adjust goal height from 8' to 10' and operate from floor level using a removable hand crank. This unit may be installed on any ADP Lemco basketball units as well as many by other manufacturers.

SPECIFICATION

Vertical tubing shall allow the slide tubing to move freely without binding. Horizontal structure are two 2" x 4" x 1/8" thick steel L braces, one at each end. A 3 1/2" x 3/4" x 1/8" thick steel c-channel is used as a direct goal attachment to transfer loads from backboard to the surrounding framework. All components are welded to insure stability during normal play. Screw rod shall be hardened 5/8" diameter stub acme thread design. Height is adjusted with hand held removable crank. Height adjustment label located inside the slide channel and viewable from the back of the unit shall be used to visually determine height settings from 8' to 10' in 3" increments.

Unit shall include a spring loaded lock located on the rod on the lower brace. This locks the rod in place when the unit is not being controlled by the crank handle. Units without a manual locking mechanism shall not be considered as equal.

Unit shall be furnished with standard flat black finish and should not be painted after shipment. Unit must be periodically lubricated to insure proper function and ease of height adjustment.