


REVISION		
REV.	DATE	BY



13702 SOUTH 200 WEST B9 PHONE (801) 280-4000
 DRAPER, UT 84020 FAX (801) 280-4040
 WWW.ADPLEMCO.COM SALES@ADPLEMCO.COM

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY THE MANUFACTURER IS STRICTLY PROHIBITED.

SCHOLASTIC VOLLEYBALL SYSTEM - 1 COURT

SIZE		SCALE		SHT. NO.		PART NO.		DWG. NO.		REV	
A		NONE		1 OF 1		6000		6000		E	

MODEL 6000

SCHOLASTIC VOLLEYBALL SYSTEM

RECOMMENDED APPLICATION

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

FLOOR SLEEVES AND COVER PLATES

Please refer to attached specification

UPRIGHTS

Upright Post shall be lightweight high strength 3 ½" O.D. aluminum. Finish shall be gray anodize. Uprights shall be removable type designed for use with below floor sleeves or above floor T-bases. Uprights shall be provided with adjustable high impact rubber foot to protect finished floors and to allow for additional precise net height adjustment. The upright post will have infinite net height adjustment for Men's, Women's, Tennis, and Badminton heights.

NET TENSIONER (WINCH)

The net tensioner shall incorporate a heavy duty, self-locking ratchet mechanism with a compression clutch brake type release. A high tensile nylon strap will be used with the winch to achieve required net tension.

NET

Net features include 1" diameter wood dowel and 4" square black nylon mesh (250-lbs tensile strength) for excellent performance and durability. Free floating net along 1/8" diameter steel 7 x 19 cable (1,760-lbs. Minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with metallic clips are used to secure net in place. Net shall be 32' length and 39" width. Net perimeter shall have a 2" wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition.

UPRIGHT PADS

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

NET ANTENNA AND TAPE

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 ½" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

AVAILABLE OPTIONS

Center Post Uprights for multi-court applications
Referee Stand with optional padding
Storage Cart

Subject to design change and current manufacturing practices.