



MODEL	FINISH	KEY REQUIRED
6430	POLISHED BRASS	YES
6431	CHROME	YES

REVISION		
REV.	DATE	BY
-	-	-



13702 SOUTH 200 WEST B9 DRAPER, UT 84020
 WWW.ADPLEMCO.COM

PHONE (801) 280-4000
 FAX (801) 280-4040
 SALES@ADPLEMCO.COM

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY THE MANUFACTURER IS STRICTLY PROHIBITED.

STANDARD SIZE LOW PROFILE FLOOR COVER

DWG. NO. 6430

SIZE A	SCALE NOTED	SHT. NO. 1 OF 1	PART NO. 6430	REV -
------------------	----------------	--------------------	-------------------------	----------

MODEL 6430
LOW PROFILE VOLLEYBALL FLOOR COVER
STANDARD SIZE

Floor cover shall be brass alloy for model 6430 and chromed steel for model 6431. Cover plate shall have a molded plastic recessed mounting flange, cork gasket, and 6 3/16" diameter cover. Molded plastic recessed mounting flange shall be 6 3/8" in diameter and have 3 holes in the ring (for screwing into the floor) that shall be completely concealed under the cover when in the closed position, allowing for a completely flat surface. In a "floating" wood floor, the floor plate is connected to the floor only, allowing it to move with the expansion and contraction of the floor. Cover shall be 6-3/16" in diameter by 1/4" thick. Diameter of opening shall be 5.25".

6430 - Polished Brass with key

6431 - Chrome with key

Subject to design change and current manufacturing practices.