



**7200 & 7205 COLLEGIATE VOLLEYBALL SYSTEM - 1 COURT**

REVISION		
REV.	DATE	BY



13702 SOUTH 200 WEST B9 DRAPER, UT 84020  
 WWW.ADPLEMCO.COM

PHONE (801) 280-4000  
 FAX (801) 280-4040  
 SALES@ADPLEMCO.COM

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY THE MANUFACTURER IS STRICTLY PROHIBITED.

**VOLLEYBALL SYSTEM**

DWG. NO. 7200 / 7205

SIZE <b>A</b>	SCALE NONE	SHT. NO. 1 OF 1	PART NO. <b>7200</b>	REV <b>C</b>
------------------	---------------	--------------------	-------------------------	-----------------

## **MODEL 7200**

### **COLLEGIATE VOLLEYBALL SYSTEM**

#### **RECOMMENDED APPLICATION**

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

#### **FLOOR SLEEVES AND COVER PLATES**

Please refer to attached specification

#### **UPRIGHTS**

Upright posts shall be 6063-T6 aluminum, 4" Diameter, 9'-6" length, post with a weight of 25 lbs. Finish shall be gray anodized. Upright posts shall be removable type with sleeves and covers and permanent fixture to the floor. Net heights shall be achieved by sliding aluminum adjustable rails to desired net height and locking rails in place with wedge type locking mechanism. Adjustable rails shall slide the full length of the post. Upright posts shall have high impact plastic caps on ends of the posts for floor protection.

#### **NET TENSIONER (WINCH)**

The net tensioner shall incorporate a heavy duty, self-locking ratchet mechanism with a compression clutch brake type release. A high tensile nylon strap will be used with the winch to achieve required net tension.

#### **NET**

Net features include 1" diameter wood dowel and 4" square black nylon mesh (250-lbs tensile strength) for excellent performance and durability. Free floating net along 1/8" diameter steel 7 x 19 cable (1,760-lbs. Minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with Velcro® backing are used to secure net in place. Net shall be 32' length and 39" width. Net perimeter shall have a 2" wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition.

#### **UPRIGHT PADS**

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

#### **NET ANTENNA AND TAPE**

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

#### **AVAILABLE OPTIONS**

Center Post Uprights for multi-court applications  
Referee Stand with optional padding  
Storage Cart

Subject to design change and current manufacturing practices.